

REFER TO DETAIL A
LP-LD-TRELLIS-03

3, .5mm thick expanded metal mesh panel,
40x20mm opening size, painted black

2700

TOW+7.83

2700

30

30mm steel pipe
support truss welded to
75x75mm MS RHS
post and MS RHS
40x75mm frame

66075mm dia. 50mm
high MS CHS
upstand plate

REFER TO DETAIL A
LP-LD-TRELLIS-03

450

150

5400

150mm dia. RC concrete column
off-form finish (cast in PVC pipes)
on RC footing to eng'r's detail @ 5400mm c/c
on a 1:24 incline

refer to TYPICAL CARPARK
PAVING PATTERN
overburnt bricks laid on edge
w/ 10mm recessed joints
with 60mm wide cement-mortar
strips on mortar bedding

TYPICAL CARPARK
& 600mm WIDE PLANTER
DETAIL

50mm RC concrete
diver on footing to eng'r's detail

refer to TYPICAL CARPARK
PAVING PATTERN
overburnt bricks laid on edge
w/ 10mm recessed joints
with 60mm wide cement-mortar
strips on mortar bedding

600

50

50

compact subgrade to
eng'r's detail

DETAIL SECTION X : Carpark Creeper Trellis

Scale 1:20

1:24